



## Model PSC120 Semi Finished Pressure Transducer Front End for Heavy Industry and General Purpose Industrial Applications

PSC120 Pressure Transducer Front End was developed for all types of industrial applications. The design is based on high temperature, inorganically bonded, media isolated, piezoresistive technology that offers reliable and accurate measurements under harsh environmental conditions. The robust construction of the PSC120 provides stable operation when subjected to shock and vibration. Suitable for use in transducers for OEM machinery, process control, automation, plastic and alloy injection molding machines, hydraulic pumps, etc.

State of the art design machined from a solid piece of stainless steel provides a leak-proof, all metal sealed system. There are no O-rings, welds or organics exposed to the pressure media. Features digital compensation and temperature correction for high accuracy and stability.



- Gauge Pressures
- ASIC Temperature Compensated
- Robust construction to stand high vibrations
- Recommended load resistance:>10,000 ohms
- 2 % Total Error Band
- Wetted Parts: 17-4PH SS(other material available)
- Process Fitting: see column Z

- Sample Applications:**
- Process Automation & Control
  - Plastic and Alloy injection machines
  - Test and Measurement Equipment
  - Factory Automation
  - Energy Management
  - Heavy industry

PSC120 Ordering Model NO.: PSC120-X-Y-Z-X			
X	Y	Z	X
<b>Output Type</b>	<b>Pressure Range</b>	<b>Port Type</b>	<b>Special configuration</b>
B = 0.5~4.5V (Ratiometric)	3 = 100 psi 4 = 250 psi	1 = 1/8-27 NPT 2 = 1/4-18 NPT	Consult factory
C = 4~20mA	5 = 500 psi	3 = DIN3852-A-G1/4	
D = 1.0~5.0V	6 = 1000 psi	4 = DIN3852-E-G1/4	
E = 0.5~4.5V	7 = 2500 psi	5 = DIN3852-A-M10*1.0	
X = Special	8 = 5000 psi 9 = 10000 psi	6 = DIN3852-A-M12*1.5 7 = 7/16-20 UNF	
	X = Special	X = Special	

Electrical data	PSC120-B (Ratiometric)	PSC120-C (4~20mA)	PSC120-D (1.0~5.0VDC)	PSC120-E (0.5~4.5VDC)
Supply Voltage	4.75 ~ 5.25VDC	9 ~ 32VDC	9 ~ 32VDC	9 ~ 32VDC
Output	0.5 ~ 4.5 VDC	4 ~ 20 mA	1.0~5.0 VDC	0.5 ~ 4.5 VDC
Supply Current	< 3 mA	<30 mA	< 3 mA	< 3 mA
Zero Output	0.5 VDC	4 mA	1.0 VDC	0.5 VDC
Full Scale Output	4.5 VDC	20 mA	5.0 VDC	4.5 VDC



## Model PSC120 Semi Finished Pressure Transducer Front End for Heavy Industry and General Purpose Industrial Applications

Performance (specified @ 25 °C)	
Accuracy(Best fit straight line)	± 0.5% BFSL
Error	± 2.0% FS TEB
Zero/Span Offset Tolerance	± 1.5%FS
Stability (typical)	<±0.25% full scale per year
Compensated Temperature Range	-20 ~ 85 °C
Operating Temperature Range	-40 ~ 100 °C
Storage Temperature Range	-40 ~ 100 °C
Burst Pressure	3 X Full Scale
Proof Pressure	2 X Full Scale
Pressure Cycles	4 million full scale cycles



### Structure reference (Unit: Inch[mm])

