

# Pressure-Sensor.com


11751 Rock Landing Drive Suite H7 Newport News, Virginia 23606 Tel: +1 757 706-3795 Fax: +1 757 240-5860 Email: Sales@pressure-sensor.com www.pressure-sensor.com



### Model PSC633 Level Sensor for Industry and General Purpose Level Measuring Applications

erformance (specified @ 25 °C) Accuracy (Best fit straight line) ± 0.5% BFSL ± 1.0% FS Zero Offset Tolerance ± 1.5% Span Offset Tolerance ± 0.25% Per year Stability (typical) Compensated Temperature Range 0°C~55°C Operating Temperature Range -40°C∼85°C Burst Pressure 5 X Full Scale Proof Pressure 2 X Full Scale Fatigue Life 4 million full scale cycles

Structure reference (Unit: Inch)



## Note: This product has CE performance.

Model PSC633 Level Sensor for Industry and General Purpose Level Measuring Applications

PSC633 Level sensor was developed for industrial and general level measuring applications. This Oil Filled sensor provides media isoation and it is completely sealed, change to the vent tube was integrated within the special output electric cable.

Features digital compensation and temperature correction for high accuracy and stability. All Wetted parts are 316 stainless steel, Nylon and FEP.



PSC633 Ordering Model NO.: PSC633-X-Y-Z-X						
X	Y	Z				
Output Type	Pressure Range	Port Type				
B = 0.5~4.5V DC	1 = 0 to 100 mBar (G) / 1.45 Psi(G)	1 = 1/8-27 NPT				
C = 4~20mA	2 = 0 to 200 mBar (G) / 2.9 Psi(G)	2 = 1/4-18 NPT				
D = 1.0~5.0V	3 = 0 to 400 mBar (G) / 5.8 Psi(G)	3 = DIN3852-A-G1/4				
E = 0.5~4.5V	4 = 0 to 1 Bar (G) / 14.5 Psi(G)	4 = DIN3852-E-G1/4				
F = 0~10V		5 = DIN3852-A-M10*1.0				
G = 0~5V		6 = DIN3852-A-M12*1.5				
		7 = 7/16-20 UNF				
		X = Special				


Electrical data	PSC633-B (Ratiometric)	PSC633-C (4~20mA)	PSC633-D (1.0~5.0VDC)	PSC633-E (0.5~4.5VDC)	PSC633-F (0~10VDC)	PSC633-G (0~5VDC)
Supply Voltage	4.75 ~ 5.25 VDC	9 ~ 32 VDC	8 ~ 32 VDC	8 ~ 32 VDC	12 ~ 32 VDC	8 ~ 32 VDC
Output	0.5 ~ 4.5 VDC	4 ~ 20 mA	1.0 ~ 5.0 VDC	0.5 ~ 4.5 VDC	0 ~ 10 VDC	0 ~ 5 VDC
Supply Current	< 3 mA	< 30 mA	< 3 mA	< 3 mA	< 12 mA	< 3 mA
Zero Output	0.5 VDC	4 mA	1.0 VDC	0.5 VDC	0 VDC	0 VDC
Full Scale Output	4.5 VDC	20 mA	5.0 VDC	4.5 VDC	10 VDC	5 VDC

Mechanical Configuration		
Media	Compatible With 316 stainless steel, Nylon, FEP	
Housing	316 stainless steel	
Wetted Material	316 stainless steel / Nylon / FEP	
Ingress Rating	IP68	


CHINA No.1,Fifth Road,YangYong Industrial Park,ShaPu Community,SongGang,BaoAn District,ShenZhen. Tel: +86 755 2699-9300 Fax: +86 755 2699-9309 Email: Sales@pressure-sensor.com EUROPE + 44 7771 995771 Email: Sales@pre

## Pressure-Sensor.com

www.pressure-sensor.com







ELECTRICAL CONNECTIONS		
Pin 1	Supply+	
Pin 2	PE	
Pin 3	Supply-	
Pin 4	Output	